


2020

# MULE PRO-DXT™ DIESEL

**Kawasaki**  
Let the Good Times Roll®



 SUPER BLACK



## POWER

|                         |   |
|-------------------------|---|
| Engine                  | 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel                              |
| Displacement            | 993cc   |
| Maximum Torque          | 38.3 lb-ft @ 2400 rpm   |
| Bore x Stroke           | 2.91x3.03 in  |
| Compression Ratio       | 23.5:1  |
| Fuel System             | Bosch in-line injection pump  |
| Transmission            | Continuously Variable Transmission (CVT) with (H,L,N,R)                       |
| Final Drive             | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock |
| Engine Braking          | Yes   |
| Alternator Output (max) | 55 amp  |

|                              |   |
|------------------------------|---|
| Ground Clearance             | 10.2 in   |
| Fuel Capacity                | 7.9 gal   |
| Turning Radius               | 16.0 ft   |
| Cargo Bed Dimensions (LxWxH) | 42.7 x 53.7 x 11.0 in (3-person) 22.0 x 53.7 x 11.0 in (6-person) |
| Cargo Bed Load Capacity      | 1000 lb (3-person) 350 lb (6-person)                              |
| Payload Capacity             | 1581 lb   |
| Seating Capacity             | 3-person (1 row), 6 person (2 row)                                |
| Towing Capacity              | 2000 lb   |
| Lighting                     | (2) Halogen headlights, (2) Halogen tail/brake lights             |

## CAPABILITY

|                                 |                                     |
|---------------------------------|-------------------------------------|
| Front Suspension / Wheel Travel | Double wishbone/8.7 in              |
| Rear Suspension / Wheel Travel  | Double wishbone/8.5 (L) /8.7 (R) in |
| Front Tires                     | 26x9.00-12                          |
| Rear Tires                      | 26x11.00-12                         |
| Steering                        | Rack-and-pinion, Tilt steering      |
| Park Brake Type                 | Independent, Mechanical Disc        |
| Front Brakes                    | Dual Disc, 2 piston caliper         |
| Rear Brakes                     | Dual Disc, 1 piston caliper         |

## DETAILS

|                |  |
|----------------|--|
| Overall Length | 133.3 in   |
| Overall Width  | 64.0 in  |
| Overall Height | 77.6 in  |
| Curb Weight    | 1922.8 lb*   |
| Wheelbase      | 92.3 in  |
| Instruments    | Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps |
| Color Choices  | Super Black  |
| Warranty       | Kawasaki 3-Year Limited Warranty   |

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [hawaii.kawasaki.com](http://hawaii.kawasaki.com) for full product details.