VULCAN® 900 CLASSIC









POWER

Engine 4-stroke, 55° V-twin, 4 valves per cylinder,

SOHC, liquid-cooled

Displacement 903cc/55.10 cu in

9.5:1

Bore x Stroke 88.0 x 74.2mm

Compression Ratio

Maximum

58.2 lb-ft @ 3500 rpm

Torque

Fuel System DFI® 34mm throttle bodies (2), with sub-

throttle valves

Ignition TCBI with digital advance

Transmission 5-speed with positive neutral finder

Final Drive Kevlar-reinforced belt

PERFORMANCE

Front
Suspension /
Wheel Travel

41mm hydraulic telescopic fork/5.9 in

Rear Suspension / Wheel Travel Uni-Trak® swingarm, 7-way adjustable

spring preload/4.1 in

Front Tire 130/90x16

Rear Tire 180/70x15

Front Brakes Single 300mm hydraulic disc

Rear Brakes Single 270mm hydraulic disc

DETAILS

Frame Type Semi-double cradle, high-tensile steel

Rake/Trail 25/4.3 in

Overall Length 97.0 in

Overall Width 39.6 in

Overall Height 41.9 in

Ground 5.3 in Clearance

Seat Height 26.8 in

Curb Weight 619.6 lb*

Fuel Capacity 5.3 gal

Wheelbase 64.8 in

Color Choices Phantom Blue/ Pearl Blizzard White

Warranty 12 Month Limited Warranty



