

2021
KLX® 230R

Kawasaki
 Let the Good Times Roll®



 LIME GREEN



POWER

| | |
|--------------------------|---|
| Engine | 4-stroke single, SOHC, air-cooled |
| Displacement | 233cc |
| Bore x Stroke | 67.0 x 66.0mm |
| Compression Ratio | 9.4:1 |
| Fuel System | DFI® with 32mm Keihin throttle body |
| Ignition | TCBI Electronic Advance |
| Transmission | 6-speed, return shift with wet multi-disc manual clutch |
| Final Drive | Chain |

| | |
|---------------------|--|
| Rear Tire | 100/100-18 |
| Front Brakes | Single 240mm petal disc with a dual-piston caliper |
| Rear Brakes | Single 220mm petal disc with single-piston caliper |

PERFORMANCE

| | |
|--|---|
| Front Suspension / Wheel Travel | 37mm telescopic fork/9.8 in |
| Rear Suspension / Wheel Travel | Uni-Trak® linkage system and single shock with adjustable spring preload/9.9 in |
| Front Tire | 80/100-21 |

DETAILS

| | |
|-------------------------|---|
| Frame Type | High-tensile steel, box-section perimeter |
| Rake/Trail | 26.5° / 4.4 in |
| Overall Length | 80.5 in |
| Overall Width | 33.1 in |
| Overall Height | 47.2 in |
| Ground Clearance | 11.8 in |
| Seat Height | 36.2 in |
| Curb Weight | 253.6 lb / 262.3 lb. CA model* |
| Fuel Capacity | 1.7 gal |
| Wheelbase | 53.5 in |
| Color Choices | Lime Green |
| Warranty | 6 Months |

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.