NINJA® ZX™-10R ABS KRT EDITION







P	N	V	V	F	R
					•

Engine 4-stroke, In-Line Four, DOHC, 16-valve, liquid-cooled

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression Ratio 13.0

Fuel System DFI® w/47mm Mikuni throttle bodies (4) with oval sub-

throttles, two injectors per cylinder

Ignition TCBI with digital advance and Sport-Kawasaki Traction

Control (S-KTRC)

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider

Aids

Electronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Sport Traction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management Function (KCMF)

PERFORMANCE

Front Suspension / Wheel Travel

43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in

Rear Suspension / Wheel Travel Horizontal back-link with Balance Free gas-charged shock, stepless, dual-range (low-/high-speed) compression damping, stepless rebound damping, fully

adjustable spring preload/4.5 in

Front Tire 120/70 ZR17

Rear Tire 190/55 ZR17

Front Brakes Intelligent Braking (KIBS) (ABS only), Brembo dual

semi-floating 330mm discs with dual radial mounted

monobloc 4-piston calipers

Rear Brakes KIBS-controlled (ABS only), single 220mm disc with

aluminum single-piston caliper

DETAILS

Frame Type Aluminum perimeter

Rake/Trail 25.0°/4.2 in

Overall Length 82.1 in

Overall Width 29.5 in

Overall Height 46.7 in

Ground Clearance 5.3 in

Seat Height 32.9 in

Curb Weight 456.4 lb*

Fuel Capacity 4.5 gal

Wheelbase 57.1 in

Special Features Aerodynamic Downforce Generating Devices, Rideology

the App Smartphone Connectivity, TFT Instrumentation

Color Choices Lime Green / Ebony / Pearl Blizzard White

Warranty 12 Month Limited Warranty



