²⁰²⁴ KLX®110R L







Rear Tire 3.00 x 12 **POWER** 4-stroke single, SOHC, air-cooled Engine Displacement 112cc **Bore x Stroke** 53.0 x 50.6mm Compression 9.5:1 Ratio 18mm Keihin carburetor and screw type **Fuel System** throttle limiter on grip housing Ignition DC-CDI Transmission 4-speed, return shift, wet multi-disc manual clutch **Final Drive** Chain

PERFORMANCE

Front Suspension / Wheel Travel	30mm hydraulic telescopic fork/5.5 in
Rear Suspension / Wheel Travel	Swingarm with single hydraulic shock/5.2 in
Front Tire	2.50 x 14

Front Brakes	90mm mechanical drum, cable actuated
Rear Brakes	110mm mechanical drum, rod actuated
DETAILS	
Frame Type	Backbone frame, high-tensile steel
Rake/Trail	24.2°/1.9 in
Overall Length	61.4 in
Overall Width	25.6 in
Overall Height	39.0 in
Ground Clearance	10.4 in
Seat Height	28.7 in
 Curb Weight	167.5 lb*
Fuel Capacity	1.0 gal
Wheelbase	42.3 in
Color Choices	Lime Green, Battle Gray
Warranty	6 Months



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.