## 2024 **MULE PRO-MX<sup>™</sup> EPS**









Engine	4-stroke, single cylinder, SOHC, 4-valve liquid-cooled
Displacement	695cc
Maximum Torque	42.7 lb-ft @ 5,000 rpm
Bore x Stroke	102.0 x 85.0mm
Compression Ratio	10.3:1
Fuel System	DFI® with 44mm throttle body
Transmission	Continuously Variable Transmission (CVT) with centrifugal clutch, (H,L,N,R)
Final Drive	Selectable 2WD/4WD, shaft Dual mode rear differential with differential lock
Engine Braking	Yes
Alternator Output (max)	35.7 amp

## **CAPABILITY**

Front Suspension / Wheel Travel	Double wishbone/8.6 in	Overall Height	74.4 in
		Curb Weight	1,587.6 lb* / 1,589.8 lb* CA Model
Rear Suspension / Wheel Travel	Double wishbone/9.1 in	Wheelbase	78.9 in
Front Tires	25 x 8.00-12, radial	Instruments	Multi-function display includes digital speed fuel gauge, odometer, hour meter, clock, dua
Rear Tires	25 x 10.00-12, radial		meters, 2WD/4WD indicator, water temperati indicator, EPS warning indicators, neutral, re
Steering	Electric Power Steering (EPS), Tilt steering		parking indicators, differential indicator lam reminder lamps
Park Brake Type	Independent, Mechanical Disc	Color Choices	Timberline Green, Firecracker Red
Front Brakes	Dual Disc, 2 piston caliper	Warranty	Kawasaki STRONG 3-Year Limited Warranty
		warranty	Kawasaki Si Kuliu S-redi Lillilleu Waliality

Scan with camera to view videos, key features and more.



\*Requires Optional Hitch

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE<sup>TM</sup> side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.

Ground Clearance	10.6 in
Fuel Capacity	9.5 gal
Turning Radius	14.0 ft
Cargo Bed Dimensions (LxWxH)	33.4 x 44.1 x 9.1 in
Cargo Bed Load Capacity	699 lb / 600 lb CA Model
Payload Capacity	1,200 lb
Seating Capacity	2
Towing Capacity	1,500 lb
Lighting	(2) Halogen headlights. (2) LED headlights

Dual Disc, 1 piston caliper

## DETAILS

**Rear Brakes** 

Overall Length	110.0 in
Overall Width	60.0 in
Overall Height	74.4 in
Curb Weight	1,587.6 lb* / 1,589.8 lb* CA Model
Wheelbase	78.9 in
Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps
Color Choices	Timberline Green, Firecracker Red