

2024

NINJA® ZX™ -10R

Kawasaki
Let the Good Times Roll®



METALLIC FLAT SPARK BLACK/EBONY



POWER

| | |
|------------------------------|--|
| Engine | 4-stroke, In-Line Four, DOHC, 16-valve, liquid-cooled |
| Displacement | 998cc |
| Bore x Stroke | 76.0 x 55.0mm |
| Compression Ratio | 13.0:1 |
| Fuel System | DFI® with 47mm throttle bodies |
| Ignition | TCBI with Digital Advance |
| Transmission | 6-speed, return shift |
| Final Drive | Sealed chain |
| Electronic Rider Aids | Öhlins Electronic Steering Damper, Electronic Cruise Control, Power Modes, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Sport-Kawasaki TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management Function (KCMF) |

| | |
|---------------------|--|
| Front Tire | 120/70 ZR17 |
| Rear Tire | 190/55 ZR17 |
| Front Brakes | Brembo dual semi-floating 330mm discs with dual radial mounted monobloc 4-piston calipers, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only) |
| Rear Brakes | Single 220mm disc with aluminum single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only) |

DETAILS

| | |
|-------------------------|---|
| Frame Type | Aluminum perimeter |
| Rake/Trail | 25.0° / 4.1 in |
| Overall Length | 82.1 in |
| Overall Width | 29.5 in |
| Overall Height | 46.7 in |
| Ground Clearance | 5.3 in |
| Seat Height | 32.9 in |
| Curb Weight | 456.4 lb* (ABS), 452.0 lb* (non-ABS) |
| Fuel Capacity | 4.5 gal |
| Wheelbase | 57.1 in |
| Special Features | 4.3" Full-Color TFT Instrumentation, Smartphone Connectivity via RIDELOGY THE APP |
| Color Choices | Metallic Flat Spark Black/Ebony |
| Warranty | 12 Month Limited Warranty |

PERFORMANCE

| | |
|--|---|
| Front Suspension / Wheel Travel | 43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in |
| Rear Suspension / Wheel Travel | Horizontal back-link with Balance Free gas-charged shock, adjustable compression damping, adjustable rebound damping, stepless adjustable spring preload/4.5 in |

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.