2024 **VULCAN[®] S**







DETAILS

	46.3 lb-ft @ 6,600 rpm	DEIMEO	
		Frame Type	High-tensile steel diamond frame
n	DFI® with 38mm throttle bodies (2), with sub- throttle valves	Rake/Trail	31° /4.7 in
	TCBI with Electronic Advance	Overall Length	90.9 in
on	6-speed with positive neutral finder	Overall Width	34.6 in
	Sealed chain	Overall Height	43.3 in
Rider	Economical Riding Indicator, Anti-lock Brake System (ABS)	Ground Clearance	5.1 in
		Seat Height	27.8 in
RMANCE		Curb Weight	498.3 lb* (ABS), 491.7 lb* (non-ABS)
	41mm telescopic fork/5.1 in	Fuel Capacity	3.7 gal
n / vel		Wheelbase	62.0 in
n /	Lay-down offset rear shock with linkage and adjustable preload/3.2 in	Color Choices	Pearl Sand Khaki/Ebony, Metallic Flat Spark Black
vel		Warranty	12 Month Limited Warranty

POWER

Engine

-	
Displacement	649cc
Bore x Stroke	83.0 x 60.0mm
Compression Ratio	10.8:1
Maximum Torque	46.3 lb-ft @ 6,600 rpm
Fuel System	DFI® with 38mm throttle bodies (2), with sub- throttle valves
Ignition	TCBI with Electronic Advance
Transmission	6-speed with positive neutral finder
Final Drive	Sealed chain
Electronic Rider Aids	Economical Riding Indicator, Anti-lock Brake System (ABS)

4-stroke, 2-cylinder, DOHC, liquid-cooled

PERFO

Suspension Wheel Trave Rear **Suspension**

Wheel Trave

Front

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.