







POWER		
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled	
Displacement	649cc	
Bore x Stroke	83.0 x 60.0mm	
Compression Ratio	10.8:1	
Maximum Torque	48.5 lb-ft @ 6,500 rpm	
Fuel System	DFI® with Keihin 36mm throttle bodies	
Ignition	TCBI with Electronic Advance	
Transmission	6-speed, return shift	
Final Drive	Sealed chain	
Electronic Rider Aids	Economical Riding Indicator, Kawasaki TRaction Control (KTRC - 3 Modes), Anti-lock	

Rear Tire	160/60 ZR17
Front Brakes	Dual 300mm petal-style discs with two-piston calipers, (and ABS)
Rear Brakes	Single 220mm petal-style disc, (and ABS)

	,	
Front Brakes	Dual 300mm petal-style discs with two-piston calipers, (and ABS)	
Rear Brakes	Single 220mm petal-style disc, (and ABS)	
DETAILS		
Frame Type	Trellis, high tensile steel	
Rake/Trail	24.0°/3.9 in	

80.9 in

30.1 in

Overall Height	41.9 in
Ground Clearance	5.1 in
Seat Height	31.1 in
Curb Weight	414.5 lb* (ABS) / 412.3 lb* (non-ABS) 50-State Model
Fuel Capacity	4.0 gal
Wheelbase	55.5 in
Special Features	Smartphone Connectivity via RIDEOLOGY THE APP, TFT Instrumentation
Color Choices	Candy Persimmon Red/Ebony, Metallic Matte Dark Gray/Metallic Spark Black
Warranty	12 Month Limited Warranty

PERFORMANCE

Front Telescopic fork/4.9 in Suspension / **Wheel Travel Rear Suspension** Horizontal back-link with adjustable preload, / Wheel Travel swingarm/5.1 in 120/70 ZR17 **Front Tire**

Brake System (ABS)





Overall Length

Overall Width