

2025

TERYX KRX® 1000 BLACKOUT EDITION

Kawasaki

Let the Good Times Roll®



 FLAT EBONY

POWER		Cargo Bed Dimensions (LxWxH)	
Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled	Cargo Bed Load Capacity	351 lb
Displacement	999cc	Payload Capacity	781 lb
Maximum Torque	76.7 lb-ft @ 7,000 rpm	Seating Capacity	2
Bore x Stroke	92.0 x 75.1mm	Towing Capacity	N/A
Compression Ratio	11.5:1	Lighting	(2) LED headlights, (2) LED taillights, LED stoplight, (4) LED light bars
Fuel System	DFI® with (2) 50mm throttle bodies	DETAILS	
Ignition	TCBI with Electronic Advance	Frame	Ladder type, tubular steel
Starting System	Electric	Overall Length	133.3 in
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)	Overall Width	68.1 in
Final Drive	Selectable 2WD/4WD with locking front differential, shaft	Overall Height	76.0 in
Engine Braking	Yes	Curb Weight	2,030.8 lb* / 2,033.0 lb* CA Model
CAPABILITY		Wheelbase	98.8 in
Front Suspension / Wheel Travel	Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in	Instruments	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in	Additional Features	LED light bars (38-in mounted to front of roof, 8-in mounted to front bumper, (2) 8-in mounted to rear of roof), Front Bumper, Rear Bumper, Steel skid-plates w/ drain holes, KQR™ Premium Roof, Hifonics® Audio System, WARN® VRX 45 Powersport Winch
Front Tires	Maxxis® Carnivore 31 x 10.00R15 8PR	Color Choices	Flat Ebony
Rear Tires	Maxxis® Carnivore 31 x 10.00R15 8PR	Warranty	6 Month Limited Warranty
Steering	Electric Power Steering (EPS) / rack-and-pinion		
Front Brakes	Dual hydraulic discs with 2-piston calipers		
Rear Brakes	Dual hydraulic discs with single-piston calipers		
Ground Clearance	14.0 in (max), 13.4 in (std)		
Fuel Capacity	10.6 gal		
Turning Radius	20.3 ft		

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.