

2026

BRUTE FORCE® 450 4x4 EPS

Kawasaki

Let the Good Times Roll®



- GRAYISH BLUE
- FIRECRACKER RED



POWER		Steering	
Engine	4-stroke, single-cylinder, SOHC, liquid-cooled	Turning Radius	Conventional tie-rod w/ Electric Power Steering (EPS)
Displacement	443cc	Towing Capacity	10.2 ft
Bore x Stroke	89.0 x 71.2mm	Total Rack Capacity	1,050 lb
Compression Ratio	9.1:1	Rack Capacity, Front/Rear	225 lb
Maximum Horsepower	32.0 hp ¹ @ 7,000 rpm	Lighting	75/150 lb
Maximum Torque	24.6 lb-ft @ 6,500 rpm		LED headlights, LED handlebar mounted light, Halogen taillight
Fuel System	FI with 38mm throttle body	DETAILS	
Ignition	Digital DC-CDI	Frame Type	Double-cradle, high-tensile tubular steel
Transmission	Automatic Continuously Variable Transmission (CVT) with centrifugal clutch (H,L,N,R)	Tread Width	35.8/34.2 in
Final Drive	Selectable 2WD/4WD with dual-mode front differential, shaft	Overall Length	80.1 in
CAPABILITY		Overall Width	43.3 in
Front Suspension / Wheel Travel	Dual A-arm, adjustable spring preload/7.6 in	Overall Height	46.7 in
Rear Suspension / Wheel Travel	Dual A-arm, adjustable spring preload/7.9 in	Seat Height	34.6 in
Front Tires	AT 24 x 8-12	Estimated Dry Weight	672.5 lb** / 674.7 lb** CA Model
Rear Tires	AT 24 x 10-12	Curb Weight	712.2 lb* / 714.4 lb* CA Model
Front Brakes	Dual 202mm discs	Wheelbase	47.8 in
Rear Brakes	Single 202mm disc	Instruments	Speedometer, tachometer, gear position indicator, fuel gauge, clock, odometer, hour meter, trip meter, Differential Lock/4WD indicator, etc.
Ground Clearance	9.3 in	Special Features	KQR™ system-compatible front and rear cargo racks with carrier covers
Starting System	Electric	Color Choices	Grayish Blue, Firecracker Red
Fuel Capacity	4.2 gal	Warranty	12 Month Limited Warranty
		Kawasaki Protection Plus™ (optional)	12, 24, 36 or 48 months

Scan with camera to view videos, key features and more.

¹Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied)

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit hawaii.kawasaki.com for full product details.