

2026

ELIMINATOR[®] SE ABS

Kawasaki
Let the Good Times Roll[®]



METALLIC IMPERIAL RED/EBONY



POWER

Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled
Displacement	451cc
Bore x Stroke	70.0 x 58.6mm
Compression Ratio	11.3:1
Maximum Horsepower	51 hp ¹ @ 10,000 rpm
Maximum Torque	31.7 lb-ft @ 7,500 rpm
Fuel System	DFI [®] with 32mm throttle bodies
Ignition	TCBI w/ Digital Advance
Transmission	6-speed, return shift
Final Drive	Sealed chain
Electronic Rider Aids	Anti-lock Brake System

PERFORMANCE

Front Suspension / Wheel Travel	41mm telescopic fork/4.7 in
Rear Suspension / Wheel Travel	Twin shocks/3.1 in
Front Tire	130/70-18
Rear Tire	150/80-16

Front Brakes	Single 310mm disc with twin-piston caliper, and ABS
Rear Brakes	Single 220mm disc with single-piston caliper, and ABS

DETAILS

Frame Type	Trellis, high-tensile steel
Rake/Trail	30.0° / 4.8 in
Overall Length	88.6 in
Overall Width	30.9 in
Overall Height	43.3 in
Ground Clearance	5.9 in
Seat Height	28.9 in
Estimated Dry Weight	363.8 lb ^{**}
Curb Weight	390.3 lb [*]
Fuel Capacity	3.4 gal
Wheelbase	59.8 in
Special Features	ERGO-FIT [®] , Smartphone Connectivity via RIDEOLOGY THE APP
Color Choices	Metallic Imperial Red/Ebony
Warranty	12 Month Limited Warranty

Scan with camera
to view videos,
key features
and more.



^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit hawaii.kawasaki.com for full product details.