

2026

KLX®110R L



- LIME GREEN
- BRIGHT WHITE



POWER		Rear Tire	3.00 x 12
Engine	4-stroke, single-cylinder, SOHC, air-cooled	Front Brakes	90mm mechanical drum, cable actuated
Displacement	112cc	Rear Brakes	110mm mechanical drum, rod actuated
Bore x Stroke	53.0 x 50.6mm	DETAILS	
Compression Ratio	9.5:1	Frame Type	Backbone frame, high-tensile steel
Fuel System	Keihin PB18 carburetor and screw type throttle limiter on grip housing	Rake/Trail	24.2° / 1.9 in
Ignition	DC-CDI	Overall Length	61.4 in
Transmission	4-speed, return shift, wet multi-disc manual clutch	Overall Width	25.6 in
Final Drive	Chain	Overall Height	39.0 in
PERFORMANCE		Ground Clearance	10.4 in
Front Suspension / Wheel Travel	30mm hydraulic telescopic fork/5.5 in	Seat Height	28.7 in
Rear Suspension / Wheel Travel	Swingarm with single hydraulic shock/5.2 in	Estimated Dry Weight	158.7 lb**
Front Tire	2.50 x 14	Curb Weight	167.5 lb*
		Fuel Capacity	1.0 gal
		Wheelbase	42.3 in
		Color Choices	Lime Green, Bright White
		Warranty	6 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.
*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit hawaii.kawasaki.com for full product details.