

2026  
KX™112



LIME GREEN



POWER

|                   |                                                                          |
|-------------------|--------------------------------------------------------------------------|
| Engine            | 2-stroke, single-cylinder with exhaust power valve (KIPS), liquid-cooled |
| Displacement      | 112cc                                                                    |
| Bore x Stroke     | 52.5 x 51.6mm                                                            |
| Compression Ratio | 9.9:1 (low speed) / 8.6:1 (high speed)                                   |
| Fuel System       | 28mm Keihin carburetor                                                   |
| Ignition          | CDI with digital advance                                                 |
| Transmission      | 6-speed, return shift, with wet multi-disc manual clutch                 |
| Final Drive       | Chain                                                                    |

PERFORMANCE

|                                 |                                                                                                                                            |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Front Suspension / Wheel Travel | 43mm inverted fork with adjustable compression and rebound damping/10.8 in                                                                 |
| Rear Suspension / Wheel Travel  | Uni-Trak® single shock with adjustable dual-range (high-low-speed) compression and rebound damping, plus adjustable spring preload/12.0 in |
| Front Tire                      | 70/100-19                                                                                                                                  |

|              |                                                    |
|--------------|----------------------------------------------------|
| Rear Tire    | 90/100-16                                          |
| Front Brakes | Single 240mm petal disc with dual-piston caliper   |
| Rear Brakes  | Single 220mm petal disc with single-piston caliper |

DETAILS

|                  |                                    |
|------------------|------------------------------------|
| Frame Type       | Perimeter, high-tensile steel      |
| Rake/Trail       | 29.2° / 4.6 in                     |
| Overall Length   | 76.2 in                            |
| Overall Width    | 31.5 in                            |
| Overall Height   | 45.9 in                            |
| Ground Clearance | 13.0 in                            |
| Seat Height      | 34.1 in                            |
| Curb Weight      | 164.9 lb* without fuel / 172.8 lb* |
| Fuel Capacity    | 1.32 gal                           |
| Wheelbase        | 51.6 in                            |
| Special Features | ERGO-FIT®                          |
| Color Choices    | Lime Green                         |

Scan with camera  
to view videos,  
key features  
and more.



\*Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.  
\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.  
Specifications subject to change. Visit hawaii.kawasaki.com for full product details.