

UPDATED 2026

RIDGE® CREW HVAC CAMO

TRUETIMBER® STRATA

POWER		Fuel Capacity	12.9 gal
Engine	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled	Turning Radius	19.0 ft
Displacement	999cc	Cargo Bed Dimensions (LxWxH)	34.6 x 49.0 x 12.8 in
Maximum Horsepower	116.0 hp ¹ @ 8,500 rpm	Cargo Bed Load Capacity	1,000/600 lb CA Model
Maximum Torque	73.8 lb-ft @ 8,000 rpm	Payload Capacity	1,290 lb
Bore x Stroke	73.4 x 59.0mm	Seating Capacity	6-person (2 row), bench seats
Compression Ratio	10.6:1	Towing Capacity	2,500 lb
Fuel System	EFI	Lighting	All-LED lighting
Ignition	TCBI with Digital Advance	DETAILS	
Starting System	Electric	Frame	Ladder type, tubular steel
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Overall Length	156.7 in
Final Drive	Selectable 4WD with locking front/rear differential, shaft	Overall Width	64.0 in
Engine Braking	Yes	Overall Height	83.1 in
Alternator Output (max)	85 amp	Estimated Dry Weight	2,374.8/2,377.0 lb** CA Model
Electronic Rider Aids	Power Modes, Economical Riding Indicator	Curb Weight	2,485.0/2,487.2 lb* CA Model
CAPABILITY		Wheelbase	122.2 in
Front Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature)
Rear Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Additional Features	Full Cab with HVAC, Adjustable driver's seat, Front stabilizer bar, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR™ system compatible
Front Tires	SUNF 30 x 10-14	Color Choices	TRUETIMBER® STRATA
Rear Tires	SUNF 30 x 10-14	Warranty	Kawasaki STRONG 3-Year Limited Warranty
Wheel Type	14" Aluminum		
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)		
Front Brakes	Dual hydraulic 249mm discs with two-piston calipers		
Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers		
Ground Clearance	14.4/15.2 in (max preload); 14.4 in CA Model		

Scan with camera to view videos, key features and more.

^{*}Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

^{**}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

^{***}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

™/® & © 2026 TrueTimber Outdoors Holding Company, LLC. Manufactured and/or distributed under official license by Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.