2026

TERYX KRX® 1000 ROCK EDITION

Kawasaki
Let the Good Times Roll®

MATTE DARK BEIGE/BROWNISH ORANGE

POWER

Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled
Displacement	999cc
Maximum Horsepower	110.0 hp[1] @ 8,500 rpm
Maximum Torque	75.2 lb-ft @ 7,000 rpm
Bore x Stroke	92.0 x 75.1mm
Compression Ratio	11.5:1
Fuel System	DFI® with (2) 50mm throttle bodies
Ignition	TCBI with electronic advance
Starting System	Electric
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)
Final Drive	Selectable 2WD/4WD with locking front differential, shaft
Engine Braking	Yes

CAPABILITY

Front Suspension / Wheel Travel	Double wishbone, FOX 2.5 Podium LSC piggyback shocks, fully adjustable preload, and 24-position adjustable compression damping/18.6 in
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, FOX 2.5 Podium LSC piggyback shocks, fully adjustable preload, and 24-position adjustable compression damping/21.1 in
Front Tires	Maxxis® Roxxzilla 32 x 10.00R15 8PR
Rear Tires	Maxxis® Roxxzilla 32 x 10.00R15 8PR
Steering	Electric Power Steering (EPS) / rack-and-pinion
Front Brakes	258mm dual hydraulic discs with 2-piston calipers
Rear Brakes	258mm dual hydraulic discs with single-piston calipers
Ground Clearance	14.6 in (max) / 14.2 in (std)

Fuel Capacity	10.6 gal
Turning Radius	20.3 ft
Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in
Cargo Bed Load Capacity	351 lb
Payload Capacity	781 lb
Seating Capacity	2
Towing Capacity	N/A
Lighting	(2) LED headlights, (2) LED taillights, LED stoplight

DETAILS

Frame	Ladder type, tubular steel
Overall Length	133.3 in
Overall Width	70.1 in
Overall Height	77.8 in
Estimated Dry Weight	1,953.6 lb* / 1,955.8 lb** CA Model
Curb Weight	2,052.9 lb* / 2,055.1 lb* CA Model
Wheelbase	98.8 in
Instruments	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp
Additional Features	KQR™ Sport Roof, F/R Tow Hooks, High Molecular Weight (HMW) polyethylene skid plates & front A-arm/trailing arm guards, WARN® VRX 45-S Powersport Winch
Color Choices	Matte Dark Beige/Brownish Orange
Warranty	6 Month Limited Warranty

Scan with camera to view videos, key features and more.

‡Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.
*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
[1]This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit hawaii.kawasaki.com for full product details.