²⁰²⁰ **KLX[®] 230 ABS**







4.10 x 18

POWER

| | | Front Brakes | Single 265mm petal disc with a dual- |
|---------------------------------------|---|-----------------------|--|
| Engine | 4-stroke single, SOHC, air-cooled | | piston caliper |
| Displacement | 233cc | Rear Brakes | Single 220mm petal disc with single- piston caliper |
| Bore x Stroke | 67.0 x 66.0mm | DETAILS | |
| Compression Ratio | 9.4:1 | | |
| Fuel System | DFI® with 32mm Keihin throttle body | Frame Type | High-tensile steel perimeter |
| Ignition | TCBI Electronic Advance | Rake/Trail | 27.5°/4.6 in |
| Transmission | 6-speed, return shift with wet multi-disc manual clutch | Overall Length | 82.9 in. |
| | | Overall Width | 32.9 in. |
| Final Drive | Chain | Overall Height | 45.9 in. |
| PERFORMANCE | | Ground Clearance | 10.4 in. |
| Front Suspension / Wheel Travel | 37mm telescopic fork/8.7 in | Seat Height | 34.8 in. |
| | | Curb Weight | 293.3 lb. / 297.7 lb. CA model* |
| Rear Suspension / Wheel Travel | Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in | Fuel Capacity | 2.0 gal. |
| | | Wheelbase | 54.3 in. |
| Front Tire | 2.75 x 21 | Color Choices | Lime Green |

Rear Tire



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.

12 Months

Warranty