





PUWEK	
Engine	2-stroke single with exhaust power valve, liquid-cooled

99cc

Bore x Stroke 52.5 x 45.8mm

Ratio

Fuel System 28mm Keihin carburetor

Ignition CDI with digital advance

Transmission 6-speed, return shift, with wet multi-disc manual clutch

10.2:1 (low speed) - 8.7:1 (high speed)

manual clutch

Final Drive Chain

Displacement

Compression

PERFORMANCE

Front 36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in Wheel Travel

Rear
Suspension / Uni-Trak® gas charged shock with piggyback reservoir with 24-way compression and 21-way rebound damping plus adjustable spring preload/10.8 in

Front Tire 70/100-19

Rear Tire	90/100-16
Front Brakes	Single 220mm petal disc with dual-piston caliper
Rear Brakes	Single 220mm petal disc with single-piston

caliper

DETAILS

Frame Type	High-tensile steel perimeter design withsubframe member
Rake/Trail	29° / 4.3 in
Overall Length	75.6 in
Overall Width	30.1 in
Overall Height	45.3 in
Ground Clearance	13.0 in
Seat Height	34.3 in
Curb Weight	169.7 lb*
Fuel Capacity	1.32 gal
Wheelbase	51.6 in
Color Choices	Lime Green

Not Available





Warranty