²⁰²⁰ **KX**[™]65







POWER

Engine	2-stroke single with exhaust power valve, liquid-cooled
Displacement	64cc
Bore x Stroke	45.5 x 41.6mm
Compression Ratio	8.4:1
Fuel System	24mm Mikuni carburetor
Ignition	CDI with digital advance
Transmission	6-speed, return shift, with wet multi-disc manual clutch
Final Drive	Chain

Rear Tire80/100-12Front BrakesSingle 180mm disc with single-piston
caliperRear BrakesSingle 180mm disc with single-piston
caliper

DETAILS

Frame Type Tubular, semi-double cradle	
Rake/Trail 27°/2.4 in	
Overall Length 62.6 in	
Overall Width 29.9 in	
Overall Height 37.6 in	
Ground 12.0 in Clearance	
Seat Height 29.9 in	
Curb Weight 132.2 lb*	
Fuel Capacity 1.0 gal	
Wheelbase 44.1 in	
Color Choices Lime Green	
Warranty Not Available	

PERFORMANCE

Front Suspension / Wheel Travel	33mm leading axle telescopic fork with 4- way rebound damping/8.3 in
Rear Suspension / Wheel Travel	Uni-Trak® single shock system with 4-way rebound damping and fully adjustable spring preload/9.4 in
Front Tire	60/100-14





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.