JET SKI® ULTRA® 310LX









POWER

Engine Supercharged and intercooled, 4-stroke, DOHC, four valves per cylinder, inline 4-

cylinder

Displacement 1,498cc

Bore x Stroke 83.0 x 69.2mm

Compression

Ratio

8.2:1

Induction Eaton Twin Vortices Series Roots-type

supercharger with air-to-water intercooler

Maximum Boost 16.8 psi

Cooling System Inducted water

Fuel System DFI® with 60mm throttle body

Ignition TCBI with digital advance

Starting System Electric

Propulsion

System System

160mm jet pump, axial-flow, single stage

Impeller 3-blade, oval-edge stainless steel

Thrust 1890 lb

PERFORMANCE

Lubrication Semi-dry sump system

Coupling Direct drive from engine

Oil Capacity 5.8 qt.

Fuel Capacity 20.6 gal.

Load Capacity 496 lb.

Storage 56 gal. Capacity

DETAILS

Overall Length 132.7 in.

Overall Width 47.0 in.

Overall Height 49.4 in.

Curb Weight 1073.8 lb.

Seating Capacity

Color Choices Metallic Carbon Gray

3

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI CARES: Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a USCG-approved personal flotation device, eyewear, gloves, footwear, and a wet suit or clothing that provides equivalent protection (board shorts with neoprene liner). Never ride under the influence of drugs or alcohol. Respect the rights of shoreline residents and other marine recreationists. Boat smart from the start. Take a Boating Safety course; for more information visit www.USCGBoating.org. Jet Ski® watercraft are inboard powerboats and their use is subject to all applicable federal, state, and local boating laws. Read Owner's Manual and all on-product warnings. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit hawaii.kawasaki.com for full product details.