MULE 4000 TRANS™







POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V, liquid-cooled, gas

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2500 rpm

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,N,R)

Final Drive 2WD, shaft. Dual mode rear differential with

differential lock

Engine Braking Nο

(max)

Alternator Output 23 amp

CAPABILITY

MacPherson Strut/3.9 in Front Suspension / **Wheel Travel**

Rear Suspension / **Wheel Travel**

DeDion Axle/2.8 in

Independent, Mechanical Drum

Front Tires 23x11.00-10

Rear Tires 23x11.00-10

Steering Electric Power Steering (EPS)

Front Brakes

Drum

Rear Brakes Drum **Ground Clearance** 7.7 in

Fuel Capacity 6.3 gal

Turning Radius 12.8 ft 50.4 x 47.6 x 11.2 in (2-person),30.3 x 47.6 x 11.2 in (4-

Cargo Bed Dimensions (LxWxH)

800 lb (2-person),400 lb (4-person)

Cargo Bed Load

Capacity Payload Capacity 1330 lb

Seating Capacity 2-4

Towing Capacity 1200 lb

Lighting (2) Halogen headlights, (2) Halogen tail/brake lights

DETAILS

Overall Width

Overall Length 128.5 in

Overall Height 78.1 in

Curb Weight 1514.1 lb*

Wheelbase 85.2 in

Parking brake warning light, coolant temperature Instruments warning light, 12V DC outlet, fuel gauge, hour meter

Color Choices Bright White

Warrantv Kawasaki 3-Year Limited Warranty

58.5 in

Scan with camera to view videos, key features and more.

Park Brake Type

