MULE™ 4010 TRANS4x4®









POWER

4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled **Engine**

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2500 rpm

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with

(H,L,N,R)

Final Drive

differential with differential lock

Engine Braking

Alternator Output 23 amp

(max)

Selectable 2WD/4WD, shaft. Dual mode rear

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in **Wheel Travel**

Rear Suspension / Wheel Travel

DeDion Axle/2.8 in

Front Tires 23x11.00-10 **Rear Tires** 23x11.00-10

Steering Electric Power Steering (EPS)

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum **Rear Brakes** Drum **Ground Clearance** 7.1 in

Fuel Capacity 6.3 gal

Turning Radius 12.8 ft

50.4 x 47.6 x 11.2 in (2-person)30.3 x 47.6 x 11.2 in (4-**Cargo Bed Dimensions** (LxWxH)

Cargo Bed Load Capacity

800 lb (2-person)400 lb (4-person)

Payload Capacity 1330 lb

Seating Capacity 2-4

Towing Capacity 1200 lb

Lighting (2) Halogen headlights, (2) Halogen tail/brake lights

DETAILS

Overall Length 128.5 in

Overall Width 58.5 in

Overall Height 75.8 in

1586.9 lb* **Curb Weight**

Wheelbase 85.2 in

Instruments Parking brake warning light, coolant temperature

warning light, 12V DC outlet, fuel gauge, hour meter

Color Choices Timberline Green, Dark Royal Red

Warranty Kawasaki 3-Year Limited Warranty



