MULE PRO-FXT™







D	n	V	v	С	D
Г	U	٧	v	C	П

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

48.0 lb-ft @ 3500 rpm **Maximum Torque**

Bore x Stroke 2.83x2.62 in

Fuel System

Transmission

Final Drive

with differential lock

Engine Braking

Alternator Output

(max)

Compression Ratio

DFI® with 34mm throttle body

Continuously Variable Transmission (CVT) with (H,L,N,R)

Selectable 2WD/4WD, shaft. Dual mode rear differential

75 amp

CAPABILITY

Front Suspension / Double wishbone/8.7 in **Wheel Travel**

Rear Suspension / **Wheel Travel**

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires

26x9.00-12, radial 26x11.00-12, radial

Rear Tires Steering

Rack-and-pinion

Park Brake Type

Independent, Mechanical Disc

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

Ground Clearance 10.2 in

Turning Radius 16.0 ft

Cargo Bed Dimensions (LxWxH)

Fuel Capacity

42.7 x 53.7 x 11.0 in (3-person)22.0 x 53.7 x 11.0 in (6-

7.9 gal

Cargo Bed Load

Capacity

1000 lb (3-person)350 lb (6-person)(600 lb for

California models)

Payload Capacity 1616 lb (1264 lb California model)

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2000 lb

Lighting (2) Halogen headlights, (2) Halogen tail/brake lights

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.6 in

Curb Weight 1887.5 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

> fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt

reminder lamps

Color Choices Super Black

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

