2020

MULE SX™









POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled, gas

Displacement 401cc

Maximum Torque 20.6 lb-ft @ 2200 rpm

Bore x Stroke 3.23x2.99 in

Compression Ratio 8.3:1

Fuel System Nikki 6C1026 carburetor

Transmission Continuously Variable Transmission (CVT) with (H,N,R)

Final Drive 2WD, shaft. Dual mode rear differential with

differential lock

Engine Braking No

Alternator Output 17 amp

(max)

Rear Brakes Drum **Ground Clearance** 6.1 in **Fuel Capacity** 4.2 gal

Turning Radius 10.8 ft

Cargo Bed Dimensions (LxWxH)

35.6 x 40.9 x 9.6 in

Cargo Bed Load

400 lb

Capacity

926 lb

Seating Capacity

Towing Capacity

Payload Capacity

1100 lb*

Lighting

(2) Halogen headlights,(2) Halogen tail/brake lights

CAPABILITY

MacPherson Strut/3.1 in Front Suspension / **Wheel Travel**

Rear Suspension /

Unit Swingarm/3.1 in

Wheel Travel

Rack-and-pinion

Front Tires 22x9.00-10 **Rear Tires**

22x11.00-10

Park Brake Type

Steering

Independent, Mechanical Drum

Front Brakes Drum

DETAILS

Overall Length 106.7 in

Overall Width 52.6 in

Overall Height 70.1 in

Curb Weight 967.6 lb**

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

Color Choices Timberline Green, Dark Royal Red

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

