## MULE SX™ 4x4 XC FI









## **POWER**

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 21.4 lb-ft @ 2400 rpm

Bore x Stroke 3.23x2.99 in

Compression Ratio 8.6:

Fuel System Fuel injection

**Transmission** Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

22.9 amp

Engine Braking N

Alternator Output

(max)

Rear Brakes Drum

Ground Clearance 8.1 in

Fuel Capacity 4.2 gal

Turning Radius 11.8 ft

Cargo Bed Dimensions (LxWxH) 35.6 x 40.9 x 9.6 in

Cargo Bed Load Capacity

400 lb

Payload Capacity 900 lb

Seating Capacity 2

Towing Capacity 1100 lb\*

**Lighting** (2) Halogen headlights, (2) Halogen tail/brake lights

## **CAPABILITY**

Front Suspension / MacPherson Strut/3.1 in Wheel Travel

Rear Suspension / Wheel Travel Unit Swingarm/3.1 in

Front Tires 26x9.00-12

**Rear Tires** 26x9.00-12

Steering Rack-and-pinion

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum

## **DETAILS**

Warranty

Overall Length 106.7 in
Overall Width 52.6 in

Overall Height 73.4 in

Curb Weight 1082.7 lb\*\*

Wheelbase 70.1 in

**Instruments** Fuel gauge, hour meter, oil temp light, parking brake

ight

Color Choices Vibrant Blue, Timberline Green

Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



\*Requires Optional Hito