VULCAN® 1700 VAQUERO® ABS







P	N	V	N	F	R
	u		М	L	11

Engine 4-stroke, 52° V-twin, liquid-cooled

Displacement 1,700cc/103.7 cu in

Bore x Stroke 102.0 x 104.0mm

Compression

Ratio

9.5:1

Maximum Torque 107.6 lb-ft @ 2750 rpm

Fuel System

DFI® 42mm throttle bodies (2)

Ignition

TCBI with digital advance

Transmission

6-speed with overdrive and positive

neutral finder

Final Drive

Carbon fiber-reinforced belt

PERFORMANCE

Front
Suspension /
Wheel Travel

45mm hydraulic fork/5.5 in

Rear Suspension / Wheel Travel Swingarm with twin air-assisted shocks, with 4-way rebound damping/3.1 in

Front Tire 130/90x16

Rear Tire 170/70x16

Front Brakes Dual 300mm discs, dual four-piston

calipers, K-ACT II ABS

Rear Brakes Single 300mm disc, twin-piston caliper, K-

ACT II ABS

DETAILS

Frame Type Steel, double-cradle with box-section single-tube backbone

Overall Length 98.8 in

Overall Width 38.2 in

Overall Height 50.8 in

Ground Clearance 5.7 in

Seat Height 28.7 in

Curb Weight 844.5 lb*

Fuel Capacity 5.3 gal

Wheelbase 65.6 in

Color Choices Candy Imperial Blue

Warranty 36 Month Limited Warranty



