





n	n	M		n
r	U	W	ľΕ	K

Engine 4-stroke single, DOHC, liquid-cooled

Displacement 249cc

Bore x Stroke 78.0 x 52.2mm

Compression Ratio

14.1:1

Fuel System

DFI® with 44mm Keihin throttle body and

dual injectors

Ignition

Digital CDI

Transmission

5-speed, return shift, with wet multi-disc

manual clutch

Final Drive

Chain

PERFORMANCE

Front
Suspension /
Wheel Travel

48mm inverted telescopic coil spring fork with 23-way compression damping and 20-way rebound damping /12.4 in

Rear Suspension / Wheel Travel Uni-Trak® with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and

adjustable preload/12.4 in

Front Tire

80/100-21

Rear Tire	110/100-18
Front Brakes	Single semi-floating 270mm Braking® petal disc with dual-piston caliper
Rear Brakes	Single 240mm Braking® petal disc with single-piston caliper

Aluminum perimeter

27.8/4.8 in

DETAILS

Frame Type

Rake/Trail

Overall Length	85.4 in
Overall Width	32.3 in
Overall Height	49.6 in
Ground Clearance	13.0 in
Seat Height	37.2 in
Curb Weight	230.1 lb without fuel/240.2 lb*
Fuel Capacity	1.64 gal
Wheelbase	58.3 in

Lime Green

Not Available





Color Choices

Warranty