





_	_			
n	n	M	ı	R
$\boldsymbol{\nu}$		w	•	• к
		-	,	-

Engine 2-stroke single, liquid-cooled

Displacement 64cc

Bore x Stroke 45.5 x 41.6mm

Compression

8.4:1 **Ratio**

Ignition CDI with digital advance

6-speed, return shift, with wet multi-disc **Transmission**

manual clutch

24mm Mikuni carburetor **Fuel System**

Final Drive Chain

PERFORMANCE

Front Suspension / **Wheel Travel** 33mm leading axle telescopic fork with 4way rebound damping/8.3 in

Rear Suspension / **Wheel Travel** Uni-Trak® single shock system with 4-way rebound damping and fully adjustable spring preload/9.4 in

Front Tire 60/100-14

Single 180mm disc with single-piston **Front Brakes**

caliper

80/100-12

Rear Brakes Single 180mm disc with single-piston

caliper

DETAILS

Rear Tire

High-tensile steel semi-double cradle **Frame Type**

Rake/Trail 27°/2.4 in

Overall Length 62.6 in

Overall Width 29.9 in

Overall Height 37.6 in

Ground 12.0 in Clearance

Seat Height 29.9 in

Curb Weight 132.2 lb*

Fuel Capacity 1.0 gal

Wheelbase 44.1 in

Color Choices Lime Green

Not Available Warranty



