MULE PRO-MX™ EPS









POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5000 rpm

Bore x Stroke 4.02x3.35 in

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with

centrifugal clutch, (H,L,N,R)

Selectable 2WD/4WD, shaft. Dual mode rear differential **Final Drive**

with differential lock

Engine Braking

Alternator Output 35.7 amp

(max)

Rear Brakes Dual Disc, 1 piston caliper

Ground Clearance 10.6 in

Fuel Capacity 9.5 gal

Turning Radius 14.0 ft

Cargo Bed

Dimensions (LxWxH)

699 lb (600 lb California models)

33.4 x 44.1 x 9.1 in

Cargo Bed Load Capacity

Payload Capacity 1200 lb

Seating Capacity

Towing Capacity

1500 lb Lighting (2) Halogen headlights. (2) LED headlights

CAPABILITY

Front Suspension / Double wishbone/8.6 in **Wheel Travel**

Rear Suspension / Wheel Travel

Double wishbone/9.1 in

Front Tires

25x8.00-12, radial

Rear Tires

25x10.00-12, radial

Park Brake Type

Electric Power Steering (EPS), Tilt steering

Independent, Mechanical Disc

Front Brakes

Steering

Dual Disc, 2 piston caliper

DETAILS

Overall Length 110.0 in **Overall Width** 60.0 in

Overall Height 74.4 in

Curb Weight 1587.6 lb*

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt

reminder lamps

Color Choices Timberline Green, Bright White

Kawasaki 3-Year Limited Warranty Warranty

Scan with camera to view videos, key features and more.

