MULE SX[™] 4x4 FI









POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 21.4 lb-ft @ 2400 rpm

Bore x Stroke 3.23x2.99 in

Compression Ratio

Fuel System Fuel Injection

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output

(max)

Rear Brakes Drum **Ground Clearance** 6.7 in **Fuel Capacity** 4.2 gal **Turning Radius** 10.8 ft 35.6 x 40.9 x 9.6 in

Cargo Bed Dimensions (LxWxH)

Cargo Bed Load

Capacity **Payload Capacity**

915 lb

400 lb

Seating Capacity

Towing Capacity

1100 lb*

Lighting (2) Halogen headlights, tail/brake lights

CAPABILITY

Front Suspension / **Wheel Travel**

MacPherson Strut/3.1 in

Rear Suspension / Wheel Travel

Unit Swingarm/3.1 in

Front Tires

24x9.00-10

22.9 amp

Rear Tires 24x11.00-10

Steering

Rack-and-pinion, Tilt steering

Park Brake Type

Independent, Mechanical Drum

Front Brakes

Drum

DETAILS

Curb Weight

Overall Length 106.7 in

Overall Width 52.6 in

Overall Height 70.9 in

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

light / horn (SE only)

Color Choices Timberline Green, Dark Royal Red

1031.9 lb**

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

