## NINJA® ZX™-10RR







## **POWER**

Engine 4-stroke, In-Line Four, DOHC, 16-valve, liquid-

cooled

13.0:1

**Displacement** 998cc

Bore x Stroke 76.0 x 55.0mm

Compression

Ratio

Fuel System

DFI® w/47mm Mikuni throttle bodies (4) with oval sub-throttles, two injectors per cylinder

Ignition TCBI with digital advance and Sport-Kawasaki

Traction Control (S-KTRC)

Transmission 6-speed, return shift

Final Drive Sealed chain

**Electronic Rider** 

Aids

Electronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Sport Traction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management Function (KCMF)

## **PERFORMANCE**

Front Suspension / Wheel Travel

43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in

Rear Suspension / Wheel Travel

Horizontal back-link with Balance Free gascharged shock, stepless, dual-range (low-/highspeed) compression damping, stepless rebound damping, fully adjustable spring preload/4.5 in Front Tire 120/70 ZR17

**Rear Tire** 190/55 ZR17

Front Brakes Intelligent Braking (KIBS), Brembo dual semi-

floating 330mm discs with dual radial mounted

monobloc 4-piston calipers

Rear Brakes KIBS-controlled, single 220mm disc with aluminum

single-piston caliper

## **DETAILS**

Frame Type Aluminum perimeter

Rake/Trail 25.0°/4.2 in

Overall Length 82.1 in

Overall Width 29.5 in

Overall Height 46.7 in

**Ground Clearance** 5.3 in

Seat Height 32.9 in

Curb Weight 456.4 lb\*

Fuel Capacity 4.5 gal

Wheelbase 57.1 in

Special Features Pankl Pistons & Titanium Connecting Rods,

Aerodynamic Downforce Generating Devices, Rideology the App Smartphone Connectivity, TFT

Instrumentation

Color Choices Lime Green

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more.

