## **ELIMINATOR®** SE ABS









and ABS

Single 310mm disc with twin-piston caliper,

n	1	П	M		
r	u	ľ	N	r	ĸ

**Engine** 4-stroke, 2-cylinder, DOHC, liquid-cooled

Displacement 451cc

70.0 x 58.6mm **Bore x Stroke** 

Compression

Ratio

Maximum **Torque** 

31.7 lb-ft

11.3:1

**Fuel System** 

DFI 32mm Throttle Bodies

Ignition

TCBI w/ Digital Advance

**Transmission** 

6-speed, return shift

**Final Drive** 

Sealed chain

## **PERFORMANCE**

41mm telescopic fork/4.7 in Suspension / **Wheel Travel** 

**Rear Suspension** / Wheel Travel

Twin shocks/3.1 in

**Front Tire** 

130/70-18

**Rear Tire** 

150/80-16

## Single 220mm disc with single-piston caliper, and ABS **DETAILS** Trellis, high-tensile steel **Frame Type** Rake/Trail 30°/4.8 in **Overall Length** 88.6 in **Overall Width** 30.9 in **Overall Height** 43.3 in 5.9 in Ground Clearance **Seat Height** 28.9 in **Estimated Dry** 363.8 lb\*\* Weight **Curb Weight** 390.3 lb\* **Fuel Capacity** 3.4 gal Wheelbase 59.8 in **Special Features** Smartphone connectivity, RIDEOLOGY THE APP **Color Choices** Candy Steel Furnace Orange/Ebony 12 Month Limited Warranty Warranty

Scan with camera to view videos, key features and more.

'Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.

**Front Brakes** 

**Rear Brakes**