

2024 KLX[®] 230 S

Kawasaki
Let the Good Times Roll[®]



POWER

Engine	4-stroke single, SOHC, air-cooled
Displacement	233cc
Bore x Stroke	67.0 x 66.0mm
Compression Ratio	9.4:1
Maximum Torque	13.2 lb-ft @ 6,400 rpm
Fuel System	DFI [®] with 32mm throttle body
Ignition	TCBI with Electronic Advance
Transmission	6-speed
Final Drive	Sealed chain
Electronic Rider Aids	Anti-lock Brake System (ABS)

Front Brakes Single 240mm (265mm ABS Model) petal disc with a dual-piston caliper (and ABS)

Rear Brakes Single 220mm petal disc with single-piston caliper (and ABS)

DETAILS

Frame Type	Perimeter, high-tensile steel
Rake/Trail	24.6° / 3.7 in
Overall Length	81.8 in
Overall Width	33.2 in
Overall Height	44.8 in
Ground Clearance	9.4 in
Seat Height	33.2 in
Curb Weight	291.0/293.2 lb* 50-State Model
Fuel Capacity	2.0 gal
Wheelbase	53.7 in
Special Features	ERGO-FIT [®] , LCD Instrumentation with Smartphone Connectivity via RIDELOGY THE APP MOTORCYCLE
Color Choices	Lime Green, Battle Gray
Warranty	12 Month Limited Warranty

PERFORMANCE

Front Suspension / Wheel Travel	37mm telescopic fork/7.8 in
Rear Suspension / Wheel Travel	Uni-Trak [®] linkage system and single shock with adjustable spring preload/8.7 in
Front Tire	2.75 x 21
Rear Tire	4.10 x 18

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.