

2024

NINJA® 650

Kawasaki

Let the Good Times Roll®



- METALLIC MATTE DARK GRAY/METALLIC SPARK BLACK/
METALLIC FLAT SPARK BLACK
- METALLIC MATTE GRAPHENE STEEL GRAY/EBONY
- METALLIC MATTE COVERT GREEN/METALLIC SPARK BLACK/
PEARL SAND KHAKI



POWER		Rear Tire	
Engine	4-stroke, Parallel Twin, DOHC, 8-valve, liquid cooled	Front Brakes	160/60 x 17
Displacement	649cc	Rear Brakes	Dual 300mm petal-type discs and 2-piston calipers (and ABS)
Bore x Stroke	83.0 x 60.0mm		Single 220mm petal-type disc and single-piston caliper (and ABS)
Compression Ratio	10.8:1	DETAILS	
Fuel System	DFI® with dual 36mm Keihin throttle bodies	Frame Type	Trellis, high-tensile steel
Ignition	TCBI with Electronic Advance	Rake/Trail	24.0° / 3.9 in
Transmission	6-speed	Overall Length	80.9 in
Final Drive	Sealed chain	Overall Width	29.1 in
Electronic Rider Aids	Kawasaki TRaction Control (KTRC), ABS	Overall Height	45.1 in
PERFORMANCE		Ground Clearance	5.1 in
Front Suspension / Wheel Travel	41mm hydraulic telescopic fork/4.9 in	Seat Height	31.1 in
Rear Suspension / Wheel Travel	Horizontal back-link with adjustable spring preload/5.1 in	Curb Weight	423.4 lb* (ABS), 421.2 lb* (non-ABS)
Front Tire	120/70 x 17	Fuel Capacity	4.0 gal
		Wheelbase	55.5 in
		Color Choices	Metallic Matte Dark Gray/Metallic Spark Black/ Metallic Flat Spark Black, Metallic Matte Covert Green/ Metallic Spark Black/Pearl Sand Khaki, Metallic Matte Graphenesteel Gray/Ebony
		Warranty	12 Month Limited Warranty

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.