







## **POWER**

**Engine** 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement 783cc

**Maximum Torque** 47.0 lb-ft @ 5,500 rpm

**Bore x Stroke** 85.0 x 69.0mm

**Compression Ratio** 10.7:1

**Fuel System** DFI® with two 36mm Mikuni throttle bodies

TCBI with Electronic Advance Ignition

**Starting System Flectric** 

**Transmission** Automatic CVT with centrifugal clutch (H,L,N,R)

**Final Drive** Selectable 2WD/4WD with locking front differential,

shaft

**Engine Braking** Yes **Ground Clearance** 11.2 in

**Turning Radius** 16.7 ft

**Cargo Bed** 27.6 x 43.3 x 10.4 in

**Dimensions** (LxWxH)

**Fuel Capacity** 

600 lb

7.9 gal

Capacity

**Cargo Bed Load** 

**Payload Capacity** 1,109 lb

**Seating Capacity** 

**Towing Capacity** 1,300 lb

Lighting (2) halogen headlights, (2) incandescent taillights,

incandescent stoplight

## CAPABILITY

Double Wishbone; FOX Podium coil-over shocks with Front Suspension / **Wheel Travel** piggyback reservoir, adjustable preload and 24-way

compression damping/8.0 in

**Rear Suspension /** Double Wishbone; FOX Podium coil-over shocks with piggyback reservoir, adjustable preload and 24-way **Wheel Travel** 

compression damping/8.3 in

**Front Tires** Maxxis® 26 x 9-12

**Rear Tires** Maxxis® 26 x 11-12

Steering Electric Power Steering (EPS) / rack-and-pinion

**Front Brakes** Dual hydraulic discs with two-piston calipers

**Rear Brakes** Sealed, oil-bathed, multi-disc

## **DETAILS**

Steel Tube Double-X Reinforcement **Frame** 

**Overall Length** 118.1 in **Overall Width** 60.0 in

**Overall Height** 75.8 in

**Curb Weight** 1,570.0 lb\* / 1,572.2 lb\* CA Model

Wheelbase 85.8 in

Instruments Multi-function digital meter with speedometer, fuel gauge, clock, hour meter, odometer, dual trip meter

and parking-brake indicator, R/N/P/4WD, water temp

and low-oil-pressure indicators

**Color Choices** Metallic Moondust White/Super Black

Kawasaki Strong 3-Year Limited Warranty Warranty



