2024
TERYX4™ S SE

● CANDY PERSIMMON RED

POWER

Engine	4-stroke, SOHC, 4-valve V-twin, liquid-cooled
Displacement	783cc
Maximum Torque	47.0 lb-ft @ 5,500 rpm
Bore x Stroke	85.0 x 69.0mm
Compression Ratio	10.7:1
Fuel System	DFI® with two 36mm Mikuni throttle bodies
Ignition	TCBI with Electronic Advance
Starting System	Electric
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)
Final Drive	Selectable 2WD/4WD with locking front differential, shaft
Engine Braking	Yes

CAPABILITY

Front Suspension / Wheel Travel	Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression damping/10.7 in
Rear Suspension / Wheel Travel	Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression damping/10.0 in
Front Tires	Maxxis® 27 x 9-14
Rear Tires	Maxxis® 27 x 11-14
Steering	Electric Power Steering (EPS) / rack-and-pinion
Front Brakes	Dual hydraulic discs with two-piston calipers
Rear Brakes	Sealed, oil-bathed, multi-disc

Ground Clearance	12.2 in (max) / 11.2 in (std)
Fuel Capacity	7.9 gal
Turning Radius	17.7 ft
Cargo Bed Dimensions (LxWxH)	17.9 x 47.6 x 8.7 in
Cargo Bed Load Capacity	249 lb
Payload Capacity	1,054 lb
Seating Capacity	4
Towing Capacity	1,300 lb
Lighting	(4) LED headlights, (2) LED taillights, LED stoplight

DETAILS

Frame	Steel Tube Double-X Reinforcement
Overall Length	125.4 in
Overall Width	62.6 in
Overall Height	80.5 in
Curb Weight	1,684.6 lb* / 1,686.8 lb* CA Model
Wheelbase	88.2 in
Instruments	Multi-function digital meter with speedometer, fuel gauge, clock, hour meter, odometer, dual trip meter and parking-brake indicator, R/N/P/4WD, water temp and low-oil-pressure indicators
Additional Features	Roof, Hifonics® Bluetooth®/AM/FM Audio System, WARN® VRX 35 Winch
Color Choices	Candy Persimmon Red
Warranty	Kawasaki Strong 3-Year Limited Warranty

Scan with camera to view videos, key features and more.