

2024

# Z H2 SE ABS

**Kawasaki**  
Let the Good Times Roll®



METALLIC MATTE GRAPHENE STEEL GRAY/EBONY/  
MIRROR COATED BLACK



## POWER

<b>Engine</b>	4-stroke, 4-cylinder, DOHC, 16-valve, liquid-cooled, supercharged
<b>Displacement</b>	998cc
<b>Bore x Stroke</b>	76.0 x 55.0mm
<b>Compression Ratio</b>	11.2:1
<b>Maximum Torque</b>	101.0 lb-ft
<b>Fuel System</b>	DFI® with 40mm throttle bodies
<b>Ignition</b>	TCBI with Digital Advance
<b>Transmission</b>	6-speed dog-ring, return shift
<b>Final Drive</b>	Sealed chain
<b>Electronic Rider Aids</b>	Kawasaki Electronic Control Suspension (KECS) with Showa Skyhook Technology, KECS Linked Integrated Riding Modes, Kawasaki Cornering Management Function (KCMF), Power Modes (3), Kawasaki Launch Control Mode (KLCM), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Engine Brake Control (KEBC), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Quick Shifter (KQS) (upshift & downshift), Electronic Cruise Control

<b>Rear Suspension / Wheel Travel</b>	Uni-Trak®, Showa Gas-Charged Shock with KECS Compression and KECS Damping, plus Manual Spring Preload Adjustability/5.3 in
<b>Front Tire</b>	120/70-17
<b>Rear Tire</b>	190/55-17
<b>Front Brakes</b>	Dual 320mm Disc with Radial-mount Brembo M4.32 Calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)
<b>Rear Brakes</b>	Single 260mm disc with single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)

## DETAILS

<b>Frame Type</b>	Trellis, high tensile steel
<b>Rake/Trail</b>	24.9° / 4.1in
<b>Overall Length</b>	82.1 in
<b>Overall Width</b>	31.9 in
<b>Overall Height</b>	44.5 in
<b>Ground Clearance</b>	5.5 in
<b>Seat Height</b>	32.7 in
<b>Curb Weight</b>	531.4 lb*
<b>Fuel Capacity</b>	5.0 gal
<b>Wheelbase</b>	57.3 in
<b>Special Features</b>	Smartphone Connectivity via RIDEOLGY THE APP, TFT Instrumentation
<b>Color Choices</b>	Metallic Matte Graphenesteel Gray/Ebony/Mirror Coated Black
<b>Warranty</b>	12 Month Limited Warranty

## PERFORMANCE

<b>Front Suspension / Wheel Travel</b>	Showa SFF-BP Fork with KECS Compression and KECS Rebound Damping, plus Manual Spring Preload Adjustability/4.7 in
--	---

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [hawaii.kawasaki.com](http://hawaii.kawasaki.com) for full product details.