

2025

KLX[®]230SM ABS

Kawasaki

Let the Good Times Roll[®]



 BATTLE GRAY



POWER

Engine	4-stroke single, SOHC, air-cooled
Displacement	233cc
Bore x Stroke	67.0 x 66.0mm
Compression Ratio	9.4:1
Maximum Torque	13.0 lb-ft @ 6,400 rpm
Fuel System	DFI [®] with 32mm throttle body
Ignition	TCBI with Electronic Advance
Transmission	6-speed
Final Drive	Sealed chain
Electronic Rider Aids	Anti-lock Brake System (ABS)

PERFORMANCE

Front Suspension / Wheel Travel	37mm telescopic fork/7.4 in
Rear Suspension / Wheel Travel	Uni-Trak [®] linkage system and single shock with adjustable spring preload/8.8 in
Front Tire	110/70-17
Rear Tire	120/70-17

Front Brakes	Single 300mm petal disc with a dual-piston caliper and ABS
Rear Brakes	Single 220mm petal disc with single-piston caliper and ABS

DETAILS

Frame Type	Perimeter, high-tensile steel
Rake/Trail	24.9° /3.0 in
Overall Length	80.1 in
Overall Width	33.3 in
Overall Height	44.3 in
Ground Clearance	8.7 in
Seat Height	33.1 in
Estimated Dry Weight	284.4/286.5 lb** 50-State Model
Curb Weight	299.9/302.1 lb* 50-State Model
Fuel Capacity	2.0 gal
Wheelbase	53.7 in
Special Features	ERGO-FIT [®] , LCD Instrumentation with Smartphone Connectivity via RIDELOGY THE APP MOTORCYCLE
Color Choices	Battle Gray
Warranty	12 Month Limited Warranty

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit hawaii.kawasaki.com for full product details.