

2025

MULE PRO-FXT™ 1000 LE CAMO

Kawasaki

Let the Good Times Roll®

TRUETIMBER® STRATA

| POWER                           |                                                                               |                              |                                                                                                                                                                                                                                                                                                                                            |
|---------------------------------|-------------------------------------------------------------------------------|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Engine                          | 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas                                | Rear Brakes                  | Dual disc, 1-piston caliper                                                                                                                                                                                                                                                                                                                |
| Displacement                    | 999cc                                                                         | Ground Clearance             | 12.6 in (max), 11.6 in (std)                                                                                                                                                                                                                                                                                                               |
| Maximum Torque                  | 61.5 lb-ft @ 4,500 rpm                                                        | Fuel Capacity                | 7.9 gal                                                                                                                                                                                                                                                                                                                                    |
| Bore x Stroke                   | 92.0 x 75.1mm                                                                 | Turning Radius               | 16.0 ft                                                                                                                                                                                                                                                                                                                                    |
| Compression Ratio               | 10.1:1                                                                        | Cargo Bed Dimensions (LxWxH) | 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)                                                                                                                                                                                                                                                                        |
| Fuel System                     | DFI® with 38mm throttle body                                                  | Cargo Bed Load Capacity      | 999 lb (3-person)/350 lb (6-person)/348 lb CA Model                                                                                                                                                                                                                                                                                        |
| Transmission                    | Continuously Variable Transmission (CVT) with (H,L,N,R)                       | Payload Capacity             | 1,616.3/1,263.5 lb CA Model                                                                                                                                                                                                                                                                                                                |
| Final Drive                     | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock | Seating Capacity             | 3-person (1 row), 6 person (2 row)                                                                                                                                                                                                                                                                                                         |
| Engine Braking                  | Yes                                                                           | Towing Capacity              | 2,000 lb                                                                                                                                                                                                                                                                                                                                   |
| Alternator Output (max)         | 90 amp                                                                        | Lighting                     | (2) Halogen headlights, (2) LED headlights                                                                                                                                                                                                                                                                                                 |
| CAPABILITY                      |                                                                               | DETAILS                      |                                                                                                                                                                                                                                                                                                                                            |
| Front Suspension / Wheel Travel | Double wishbone/11.0 in                                                       | Overall Length               | 135.8 in                                                                                                                                                                                                                                                                                                                                   |
| Rear Suspension / Wheel Travel  | Double wishbone/10.1 in                                                       | Overall Width                | 64.0 in                                                                                                                                                                                                                                                                                                                                    |
| Front Tires                     | 26 x 9-12, radial                                                             | Overall Height               | 80.9 in                                                                                                                                                                                                                                                                                                                                    |
| Rear Tires                      | 26 x 11-12, radial                                                            | Estimated Dry Weight         | 1,847.8/1,850.0 lb** CA Model                                                                                                                                                                                                                                                                                                              |
| Wheel Type                      | Alloy                                                                         | Curb Weight                  | 1,922.8/1,925.0 lb* CA Model                                                                                                                                                                                                                                                                                                               |
| Steering                        | Rack-and-pinion w/ Electric Power Steering (EPS), Tilt steering               | Wheelbase                    | 92.3 in                                                                                                                                                                                                                                                                                                                                    |
| Park Brake Type                 | Independent, mechanical disc                                                  | Instruments                  | Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps |
| Front Brakes                    | Dual disc, 2-piston caliper                                                   | Additional Features          | Roof, Additional Front Cup Holders                                                                                                                                                                                                                                                                                                         |
|                                 |                                                                               | Color Choices                | TRUETIMBER® STRATA                                                                                                                                                                                                                                                                                                                         |
|                                 |                                                                               | Warranty                     | Kawasaki STRONG 3-Year Limited Warranty                                                                                                                                                                                                                                                                                                    |

Scan with camera to view videos, key features and more.

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.  
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.