2025

# NINJA® 500 SE ABS

Kawasaki
Let the Good Times Roll®

- METALLIC FLAT SPARK BLACK/METALLIC SPARK BLACK/ METALLIC MOONDUST GRAY
- PASSION RED/METALLIC FLAT SPARK BLACK/ METALLIC MATTE DARK GRAY

## POWER

| | |
|---|---|
| **Engine** | 4-stroke, Parallel Twin, DOHC, liquid-cooled |
| **Displacement** | 451cc |
| **Bore x Stroke** | 70.0 x 58.6mm |
| **Compression Ratio** | 11.3:1 |
| **Maximum Torque** | 31.7 lb-ft @ 7,500 rpm |
| **Fuel System** | DFI® with dual 32mm throttle bodies |
| **Ignition** | TCBI with Digital Advance |
| **Transmission** | 6-speed |
| **Final Drive** | Sealed chain |
| **Electronic Rider Aids** | Economical Riding Indicator, Anti-lock Brake System (ABS) |

## PERFORMANCE

| | |
|---|---|
| **Front Suspension / Wheel Travel** | 41mm hydraulic telescopic fork/4.7 in |
| **Rear Suspension / Wheel Travel** | Horizontal back-link with adjustable spring preload/5.1 in |
| **Front Tire** | 110/70-17 |
| **Rear Tire** | 150/60-17 |
| **Front Brakes** | Single 310mm semi-floating disc with 2-piston calipers and ABS |
| **Rear Brakes** | Single 220mm disc with single-piston caliper and ABS |

## DETAILS

| | |
|---|---|
| **Frame Type** | Trellis, high-tensile steel |
| **Rake/Trail** | 24.7°/3.6 in |
| **Overall Length** | 78.5 in |
| **Overall Width** | 28.7 in |
| **Overall Height** | 46.5 in |
| **Ground Clearance** | 5.7 in |
| **Seat Height** | 30.9 in |
| **Estimated Dry Weight** | 348.4 lb** / 350.6 lb** 50-State Model |
| **Curb Weight** | 379.3 lb* / 381.5 lb* 50-State Model |
| **Fuel Capacity** | 3.7 gal |
| **Wheelbase** | 54.1 in |
| **Special Features** | ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP, Kawasaki's Intelligent Proximity Activation Start System (KIPASS), USB-C outlet |
| **Color Choices** | Lime Green/Ebony/Pearl Blizzard White |
| **Warranty** | 12 Month Limited Warranty |

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
[1]This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit hawaii.kawasaki.com for full product details.