

2025

RIDGE® XR CREW HVAC



- ICE GRAY
- METALLIC GRAYSTONE



| POWER                           |                                                            | FUEL CAPACITY                |                                                                                                                                                                                                                                                                                                                                                                                                               |
|---------------------------------|------------------------------------------------------------|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Engine                          | 4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled | Fuel Capacity                | 12.9 gal                                                                                                                                                                                                                                                                                                                                                                                                      |
| Displacement                    | 999cc                                                      | Turning Radius               | 19.0 ft                                                                                                                                                                                                                                                                                                                                                                                                       |
| Maximum Horsepower              | 116.0 hp <sup>1</sup> @ 8,500 rpm                          | Cargo Bed Dimensions (LxWxH) | 34.6 x 49.0 x 12.8 in                                                                                                                                                                                                                                                                                                                                                                                         |
| Maximum Torque                  | 73.8 lb-ft @ 8,000 rpm                                     | Cargo Bed Load Capacity      | 1,000/600 lb CA Model                                                                                                                                                                                                                                                                                                                                                                                         |
| Bore x Stroke                   | 73.4 x 59.0mm                                              | Payload Capacity             | 1,290/1,076 lb CA Model                                                                                                                                                                                                                                                                                                                                                                                       |
| Compression Ratio               | 10.6:1                                                     | Seating Capacity             | 4-person (2 row), bucket seats                                                                                                                                                                                                                                                                                                                                                                                |
| Fuel System                     | EFI                                                        | Towing Capacity              | 2,500 lb                                                                                                                                                                                                                                                                                                                                                                                                      |
| Ignition                        | TCBI with Digital Advance                                  | Lighting                     | All-LED lighting                                                                                                                                                                                                                                                                                                                                                                                              |
| Starting System                 | Electric                                                   | DETAILS                      |                                                                                                                                                                                                                                                                                                                                                                                                               |
| Transmission                    | Continuously Variable Transmission (CVT) with (H,L,N,R)    | Frame                        | Ladder type, tubular steel                                                                                                                                                                                                                                                                                                                                                                                    |
| Final Drive                     | Selectable 4WD with locking front/rear differential, shaft | Overall Length               | 156.7 in                                                                                                                                                                                                                                                                                                                                                                                                      |
| Engine Braking                  | Yes                                                        | Overall Width                | 64.0 in                                                                                                                                                                                                                                                                                                                                                                                                       |
| Alternator Output (max)         | 85 amp                                                     | Overall Height               | 82.7 in                                                                                                                                                                                                                                                                                                                                                                                                       |
| Electronic Rider Aids           | Power Modes, Economical Riding Indicator                   | Estimated Dry Weight         | 2,403.5/2,405.7 lb** CA Model                                                                                                                                                                                                                                                                                                                                                                                 |
| CAPABILITY                      |                                                            | Curb Weight                  | 2,513.7/2,515.9 lb* CA Model                                                                                                                                                                                                                                                                                                                                                                                  |
| Front Suspension / Wheel Travel | Long-Travel, Double Wishbone/12.7 in                       | Wheelbase                    | 122.2 in                                                                                                                                                                                                                                                                                                                                                                                                      |
| Rear Suspension / Wheel Travel  | Long-Travel, Double Wishbone/12.7 in                       | Instruments                  | Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature) |
| Front Tires                     | Duro 30 x 10-14                                            | Additional Features          | Full Cab with HVAC, Adjustable driver/passenger seats, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLGY THE APP Powersports, USB ports, KQR™ system compatible                                                                                                                                                                                                             |
| Rear Tires                      | Duro 30 x 10-14                                            | Color Choices                | Ice Gray, Metallic Graystone                                                                                                                                                                                                                                                                                                                                                                                  |
| Wheel Type                      | 14" Aluminum                                               | Warranty                     | Kawasaki STRONG 3-Year Limited Warranty                                                                                                                                                                                                                                                                                                                                                                       |
| Steering                        | Rack-and-pinion w/ Electric Power Steering (EPS)           |                              |                                                                                                                                                                                                                                                                                                                                                                                                               |
| Front Brakes                    | Dual hydraulic 249mm discs with two-piston calipers        |                              |                                                                                                                                                                                                                                                                                                                                                                                                               |
| Rear Brakes                     | Dual hydraulic 249mm discs with single-piston calipers     |                              |                                                                                                                                                                                                                                                                                                                                                                                                               |
| Ground Clearance                | 14.4/15.2 in (max preload); 14.4 in CA Model               |                              |                                                                                                                                                                                                                                                                                                                                                                                                               |

Scan with camera to view videos, key features and more.

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

Specifications subject to change. Visit [hawaii.kawasaki.com](http://hawaii.kawasaki.com) for full product details.