

2025

TERYX KRX<sup>®</sup> 1000

Kawasaki

Let the Good Times Roll<sup>®</sup>



- METALLIC SIERRA BLUE/SUPER BLACK
- METALLIC LIGHT GRAY/SUPER BLACK



POWER		Turning Radius	
Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled	Cargo Bed Dimensions (LxWxH)	20.3 ft
Displacement	999cc	Cargo Bed Load Capacity	14.6 x 33.1 x 9.1 in
Maximum Torque	76.7 lb-ft @ 7,000 rpm	Payload Capacity	351 lb
Bore x Stroke	92.0 x 75.1mm	Seating Capacity	781 lb
Compression Ratio	11.5:1	Towing Capacity	2
Fuel System	DFI <sup>®</sup> with (2) 50mm throttle bodies	Lighting	N/A
Ignition	TCBI with Electronic Advance		(2) LED headlights, (2) LED taillights, LED stoplight
Starting System	Electric	DETAILS	
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)	Frame	Ladder type, tubular steel
Final Drive	Selectable 2WD/4WD with locking front differential, shaft	Overall Length	130.1 in
Engine Braking	Yes	Overall Width	68.1 in
		Overall Height	74.8 in
		Curb Weight	1,894.1 lb* / 1,896.3 lb* CA Model
		Wheelbase	98.8 in
		Instruments	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp
CAPABILITY		Additional Features	Steel skid-plates w/ drain holes
Front Suspension / Wheel Travel	Double wishbone, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in	Color Choices	Metallic Sierra Blue/Super Black, Metallic Light Gray/Super Black
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in	Warranty	6 Month Limited Warranty
Front Tires	Maxxis <sup>®</sup> Carnivore 31 x 10.00R15 8PR		
Rear Tires	Maxxis <sup>®</sup> Carnivore 31 x 10.00R15 8PR		
Steering	Electric Power Steering (EPS) / rack-and-pinion		
Front Brakes	Dual hydraulic discs with 2-piston calipers		
Rear Brakes	Dual hydraulic discs with single-piston calipers		
Ground Clearance	14.8 in (max) / 14.2 in (std)		
Fuel Capacity	10.6 gal		

Scan with camera to view videos, key features and more.

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [hawaii.kawasaki.com](http://hawaii.kawasaki.com) for full product details.