

2026

# KLE® 500 ABS

**Kawasaki**  
Let the Good Times Roll®



METALLIC CARBON GRAY/EBONY



## POWER

<b>Engine</b>	4-stroke, Parallel Twin, DOHC, liquid-cooled
<b>Displacement</b>	451cc
<b>Bore x Stroke</b>	70.0 x 58.6mm
<b>Compression Ratio</b>	11.3:1
<b>Maximum Horsepower</b>	51 hp <sup>1</sup> @ 10,000 rpm
<b>Maximum Torque</b>	31.7 lb-ft @ 7,500 rpm
<b>Fuel System</b>	DFI® with 32mm throttle bodies
<b>Ignition</b>	TCBI with Electronic Advance
<b>Transmission</b>	6-speed, return shift
<b>Final Drive</b>	Sealed chain
<b>Electronic Rider Aids</b>	Economical Riding Indicator, Selectable On/Off Anti-lock Brake System (ABS)

<b>Rear Tire</b>	140/70-17
<b>Front Brakes</b>	Single 300mm disc with 2-piston caliper and ABS
<b>Rear Brakes</b>	Single 230mm disc with 2-piston caliper and ABS

## DETAILS

<b>Frame Type</b>	Trellis, high tensile steel
<b>Rake/Trail</b>	28.0° / 4.1 in
<b>Overall Length</b>	90.6 in
<b>Overall Width</b>	37.0 in
<b>Overall Height</b>	55.3 in (windscreen Hi) / 53.3 in (windscreen Lo)
<b>Ground Clearance</b>	7.3 in
<b>Seat Height</b>	34.3 in
<b>Estimated Dry Weight</b>	383.7 lb** / 385.9 lb** 50-State Model
<b>Curb Weight</b>	425.6 lb* / 427.8 lb* 50-State Model
<b>Fuel Capacity</b>	4.2 gal
<b>Wheelbase</b>	61.2 in
<b>Special Features</b>	LCD instrument panel, LED headlight & taillight, Adjustable windscreen, Aluminum skid plate, ERGO-FIT®, Smartphone Connectivity via RIDEOLGY THE APP MOTORCYCLE, USB Type-C outlet available as an accessory
<b>Color Choices</b>	Metallic Carbon Gray/Ebony
<b>Warranty</b>	12 Month Limited Warranty

## PERFORMANCE

<b>Front Suspension / Wheel Travel</b>	43mm inverted telescopic fork/8.3 in
<b>Rear Suspension / Wheel Travel</b>	Bottom-link Uni-Trak with adjustable spring preload/7.7 in
<b>Front Tire</b>	90/90-21

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
 \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.  
 KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.  
 Specifications subject to change. Visit [hawaii.kawasaki.com](http://hawaii.kawasaki.com) for full product details.