

2026

TERYX® KRX4™ 1000

Kawasaki

Let the Good Times Roll®



| POWER                           |                                                                                                                                                                  | DETAILS                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Engine                          | 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled                                                                                                             | Fuel Capacity                | 10.6 gal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Displacement                    | 999cc                                                                                                                                                            | Turning Radius               | 23.3 ft                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Maximum Horsepower              | 110.0 hp¹ @ 8,500 rpm                                                                                                                                            | Cargo Bed Dimensions (LxWxH) | 14.6 x 33.1 x 9.1 in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Maximum Torque                  | 75.2 lb-ft @ 7,000 rpm                                                                                                                                           | Cargo Bed Load Capacity      | 351 lb                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Bore x Stroke                   | 92.0 x 75.1mm                                                                                                                                                    | Payload Capacity             | 1,001 lb                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Compression Ratio               | 11.5:1                                                                                                                                                           | Seating Capacity             | 4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Fuel System                     | DFI® with (2) 50mm throttle bodies                                                                                                                               | Towing Capacity              | N/A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Ignition                        | TCBI with electronic advance                                                                                                                                     | Lighting                     | (2) LED headlights, (2) LED taillights, LED stoilight                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Starting System                 | Electric                                                                                                                                                         |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Transmission                    | Automatic CVT with centrifugal clutch (H,L,N,R)                                                                                                                  |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Final Drive                     | Selectable 2WD/4WD with locking front differential, shaft                                                                                                        |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Engine Braking                  | Yes                                                                                                                                                              |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| CAPABILITY                      |                                                                                                                                                                  |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Front Suspension / Wheel Travel | Double wishbone, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in                     | Frame                        | Ladder type, tubular steel                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Rear Suspension / Wheel Travel  | 4-link trailing-arm rear suspension, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in | Overall Length               | 157.3 in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Front Tires                     | Maxxis® Carnivore 31 x 10.00R15 8PR                                                                                                                              | Overall Width                | 68.1 in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Rear Tires                      | Maxxis® Carnivore 31 x 10.00R15 8PR                                                                                                                              | Overall Height               | 76.2 in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Steering                        | Electric Power Steering (EPS) / rack-and-pinion                                                                                                                  | Estimated Dry Weight         | 1,997.7 lb** / 1,999.9 lb** CA Model                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Front Brakes                    | 258mm dual hydraulic discs with 2-piston calipers                                                                                                                | Curb Weight                  | 2,099.2 lb* / 2,101.4 lb* CA Model                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Rear Brakes                     | 258mm dual hydraulic discs with single-piston calipers                                                                                                           | Wheelbase                    | 125.8 in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Ground Clearance                | 14.8 in (max), 14.2 in (std)                                                                                                                                     | Instruments                  | Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp |
|                                 |                                                                                                                                                                  | Additional Features          | Steel skid-plates w/ drain holes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|                                 |                                                                                                                                                                  | Color Choices                | Smoky Gray/Super Black, Grayish Blue/Super Black                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|                                 |                                                                                                                                                                  | Warranty                     | 6 Month Limited Warranty                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |

Scan with camera to view videos, key features and more.

¹Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [hawaii.kawasaki.com](http://hawaii.kawasaki.com) for full product details.