2023 **VULCAN® 900 CUSTOM**





PEARL MATTE SAGE GREEN/FLAT EBONY



POWER

Engine	4-stroke, 55-degree V-twin, liquid-cooled	
Displacement	903cc/55.10 cu in	
Bore x Stroke	88.0 x 74.2mm	
Compression Ratio	9.5:1	
Maximum Torque	58.2 lb-ft @ 3500 rpm	
Fuel System	DFI 34mm Throttle Bodies (2), with sub- throttle valves	
Ignition	TCBI w/ Electronic Advance	
Transmission	5-speed with positive neutral finder	
Final Drive	Kevlar-reinforced belt	

Front Tire 80/90-21 **Rear Tire** 180/70-15 Single 300mm hydraulic disc **Front Brakes** Single 270mm hydraulic disc **Rear Brakes**

DETAILS

58.2 lb-ft @ 3500 rpm	Frame Type	Semi-double cradle, high-tensile steel
	Rake/Trail	33/7.2 in
DFI 34mm Throttle Bodies (2), with sub- throttle valves	Overall Length	94.7 in
TCBI w/ Electronic Advance	Overall Width	35.2 in
5-speed with positive neutral finder	Overall Height	44.1 in
Kevlar-reinforced belt	Ground Clearance	5.5 in
	Seat Height	27.0in
ANI.F		
ANCE	Curb Weight	610.8 lb*
41mm Showa telescopic fork/5.9 in	Curb Weight Fuel Capacity	610.8 lb* 5.3 gal
41mm Showa telescopic fork/5.9 in	Ū	
	Fuel Capacity	5.3 gal
41mm Showa telescopic fork/5.9 in Uni-Trak® swingarm, 7-way adjustable	Fuel Capacity Wheelbase	5.3 gal 64.8 in

PERFORMANCE

Front
Suspension /
Wheel Travel

Rear Suspension / Wheel Travel

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.