

2024

MULE PRO-DXT™ FE DIESEL EPS

Kawasaki

Let the Good Times Roll®



POWER			
Engine	4-stroke, 3-cylinder, OHV, liquid-cooled, diesel	Ground Clearance	10.2 in
Displacement	993cc	Fuel Capacity	7.9 gal
Maximum Torque	38.3 lb-ft @ 2,400 rpm	Turning Radius	16.0 ft
Bore x Stroke	2.91 x 3.03 in	Cargo Bed Dimensions (LxWxH)	42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)
Compression Ratio	23.5:1	Cargo Bed Load Capacity	999 lb (3-person) / 350 lb (6-person)
Fuel System	Bosch in-line injection pump	Payload Capacity	1,574 lb
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Seating Capacity	3-person (1 row), 6 person (2 row)
Final Drive	Selectable 2WD/4WD, shaft Dual mode rear differential with differential lock	Towing Capacity	2,000 lb
Engine Braking	Yes	Lighting	(2) Halogen headlights.
Alternator Output (max)	55 amp		
CAPABILITY		DETAILS	
Front Suspension / Wheel Travel	Double wishbone/8.7 in	Overall Length	133.3 in
Rear Suspension / Wheel Travel	Double wishbone/8.5 in (L) / 8.7 in (R)	Overall Width	64.0 in
Front Tires	26 x 9.00-12	Overall Height	79.5 in
Rear Tires	26 x 11.00-12	Curb Weight	1,971.3 lb*
Steering	Electric Power Steering (EPS), Tilt steering	Wheelbase	92.3 in
Park Brake Type	Independent, Mechanical Disc	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps
Front Brakes	Dual Disc, 2 piston caliper	Additional Features	Roof, Horn, Universal Key, High Visibility Orange Seatbelts
Rear Brakes	Dual Disc, 1 piston caliper	Color Choices	Bright White
		Warranty	Kawasaki STRONG 3-Year Limited Warranty