





METALLIC MATTE DARK GRAY/METALLIC SPARK BLACK



| P | N | W | F | R |
|---|---|---|---|----|
| | u | | L | 11 |

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled

Displacement 649cc

Bore x Stroke 83.0 x 60.0mm

Compression

Ratio

Maximum

Torque

48.5 lb-ft @ 6,500 rpm

Fuel System DFI® with Keihin 36mm throttle bodies

Ignition TCBI with Electronic Advance

10.8:1

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider

Aids

Economical Riding Indicator, Kawasaki TRaction Control (KTRC - 3 Modes), Anti-lock

Brake System (ABS)

Front Brakes Dua

Dual 300mm petal-style discs with two-piston

calipers, (and ABS)

160/60 ZR17

Rear Brakes

Single 220mm petal-style disc, (and ABS)

DETAILS

Rear Tire

| Frame Type | Trellis, high tensile steel |
|------------|-----------------------------|
|------------|-----------------------------|

Rake/Trail 24.0°/3.9 in

Overall Length 80.9 in

Overall Width 30.1 in

Overall Height 41.9 in

Ground Clearance

5.1 in

Seat Height

31.1 in

Curb Weight

414.5 lb* (ABS) / 412.3 lb* (non-ABS) 50-State

Model

Fuel Capacity 4.0 gal

Wheelbase 55.5 in

Special Features

Smartphone Connectivity via RIDEOLOGY THE

APP, TFT Instrumentation

Color Choices

Candy Persimmon Red/Ebony, Metallic Matte Dark Gray/Metallic Spark Black

Warranty 12 Month Limited Warranty

PERFORMANCE

Front
Suspension /
Wheel Travel

Telescopic fork/4.9 in

Rear Suspension / Wheel Travel

Horizontal back-link with adjustable preload,

swingarm/5.1 in

Front Tire 120/70 ZR17

Scan with camera to view videos, key features and more.

