

2025

VULCAN® 900 CLASSIC

Kawasaki

Let the Good Times Roll®




 METALLIC CARBON GRAY/PHANTOM BLUE



POWER		Front Tire	130/90-16
Engine	4-stroke, 55-degree V-twin, liquid-cooled	Rear Tire	180/70-15
Displacement	903cc	Front Brakes	Single 300mm hydraulic disc
Bore x Stroke	88.0 x 74.2mm	Rear Brakes	Single 270mm hydraulic disc
Compression Ratio	9.5:1	DETAILS	
Maximum Torque	58.2 lb-ft @ 3,500 rpm	Frame Type	Semi-double cradle, high-tensile steel
Fuel System	DFI® with 34mm throttle bodies (2), with sub-throttle valves	Rake/Trail	32° / 6.3 in
Ignition	TCBI with Electronic Advance	Overall Length	97.0 in
Transmission	5-speed with positive neutral finder	Overall Width	39.6 in
Final Drive	Kevlar-reinforced belt	Overall Height	41.9 in
PERFORMANCE		Ground Clearance	5.3 in
Front Suspension / Wheel Travel	41mm Showa telescopic fork/5.9 in	Seat Height	26.8 in
Rear Suspension / Wheel Travel	Uni-Trak® swingarm, 7-way adjustable spring preload/4.1 in	Curb Weight	619.6 lb*
		Fuel Capacity	5.3 gal
		Wheelbase	64.8 in
		Color Choices	Metallic Carbon Gray/Phantom Blue
		Warranty	12 Month Limited Warranty

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.