

2025

BRUTE FORCE® 750 LE EPS CAMO

Kawasaki

Let the Good Times Roll®



 TRUETIMBER® STRATA



POWER		Turning Radius	10.5 ft
Engine	4-stroke, V-twin, SOHC, liquid-cooled	Towing Capacity	1,250 lb
Displacement	749cc	Total Rack Capacity	264.5 lb
Bore x Stroke	85.0 x 66.0mm	Rack Capacity, Front/Rear	88.0/176.0 lb
Compression Ratio	9.3:1	Lighting	All-LED lighting
Maximum Torque	42.7 lb-ft @ 4,750 rpm	DETAILS	
Fuel System	DFI® with two 34mm throttle bodies		
Ignition	Digital DC-CDI	Frame Type	Double-cradle, high-tensile tubular steel
Transmission	Automatic Continuously Variable Transmission (CVT) with (H,L,N,R)	Tread Width	37.0/35.6 in
Final Drive	Selectable 2WD/4WD with variable control front differential lock, shaft	Overall Length	86.0 in
CAPABILITY		Overall Width	46.1 in
		Overall Height	47.6 in
Front Suspension / Wheel Travel	Double wishbone, adjustable spring preload/6.9 in	Seat Height	35.2 in
Rear Suspension / Wheel Travel	Double wishbone, adjustable spring preload/7.4 in	Estimated Dry Weight	685.8 lb**
Front Tires	AT 25 x 8-12	Curb Weight	732.1 lb*
Rear Tires	AT 25 x 10-12	Wheelbase	50.6 in
Front Brakes	Dual hydraulic 176mm discs with 2-piston calipers	Instruments	Digital speedometer, 2WD/4WD drive indicator, fuel gauge, odometer, dual trip meters, dual hour meter, clock (12h/24h), battery voltage, Kawasaki service reminder, oil change reminder, high beam, neutral, reverse, and warning lights (engine, coolant temperature, CVT, oil, EPS, and battery voltage)
Rear Brakes	Sealed, oil-bathed, multi-disc with independent park brake	Special Features	Full-color TFT Instrumentation w/ Smartphone Connectivity via RIDEOLGY THE APP POWERSPORTS, KQR™ system
Ground Clearance	9.0 in/9.7 in (max preload)	Color Choices	TRUETIMBER® STRATA
Starting System	Electric	Warranty	12 Month Limited Warranty
Fuel Capacity	5.0 gal	Kawasaki Protection Plus™ (optional)	12, 24, 36 or 48 months
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)		

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2026 Kawasaki Motors Corp., U.S.A.

TM/® & © 2025 TrueTimber Outdoors Holding Company, LLC. Manufactured and/or distributed under official license by Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.