KLX[®]230R S









100/100-18

POWER

Engine 4-stroke, single-cylinder, SOHC, air-cooled **Displacement** 233cc

Bore x Stroke 67.0 x 66.0mm

Compression 9.4:1 **Ratio**

DFI® with 32mm Keihin throttle body **Fuel System**

TCBI with electronic advance Ignition

Transmission 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

Front Brakes

Rear Tire

piston caliper **Rear Brakes** Single 220mm petal disc with singlepiston caliper

Single 240mm petal disc with a dual-

DETAILS

High-tensile steel, box-section perimeter **Frame Type**

Rake/Trail 24.6°/3.9 in

Overall Length 80.5 in

Overall Width 33.3 in

Overall Height 46.7 in

Ground 10.6 in Clearance

Seat Height 34.4 in

Curb Weight 262.4 lb* / 264.5 lb* 50-State Model

Fuel Capacity 1.7 gal

Wheelbase 53.3 in

Color Choices Lime Green, Battle Gray

6 Month Limited Warranty Warranty

PERFORMANCE

37mm telescopic fork/8.7 in **Front** Suspension / **Wheel Travel** Uni-Trak® linkage system and single shock Rear with adjustable spring preload/8.8 in Suspension / **Wheel Travel Front Tire** 80/100-21



